

Division of Air Quality
601 57th Street SE
Charleston, WV 25304
Phone (304) 926-0475
Fax (304) 926-0479



west virginia department of environmental protection

Earl Ray Tomblin, Governor
Randy C. Huffman, Cabinet Secretary
www.dep.wv.gov

G70-C GENERAL PERMIT ENGINEERING EVALUATION

PREVENTION AND CONTROL OF AIR POLLUTION IN REGARD TO THE CONSTRUCTION, MODIFICATION,
RELOCATION, ADMINISTRATIVE UPDATE AND OPERATION OF NATURAL GAS PRODUCTION FACILITIES
LOCATED AT THE WELL SITE

APPLICATION NO.: G70-C**221**

FACILITY ID: 061-**00228**

☒ CONSTRUCTION
☐ MODIFICATION
☐ RELOCATION

☐ CLASS I ADMINISTRATIVE UPDATE
☐ CLASS II ADMINISTRATIVE UPDATE

BACKGROUND INFORMATION

Name of Applicant (as registered with the WV Secretary of State's Office): Northeast Natural Energy LLC

Federal Employer ID No. (FEIN): 27-0945493

Applicant's Mailing Address: 48 Donley Street

City: Morgantown

State: WV

ZIP Code: 26501

Facility Name: Fisher Well Pad

Operating Site Physical Address: 1003 Daybrook Road
If none available, list road, city or town and zip of facility.

City: Fairview

Zip Code: 26570

County: Monongalia

Latitude & Longitude Coordinates (NAD83, Decimal Degrees to 5 digits):

Latitude: 39.69611

Longitude: -80.21369

SIC Code: 1311

NAICS Code: 211111

Date Application Received:

September 7, 2016

Fee Amount: \$1,500

Date Fee Received: September 12, 2016

Applicant Ad Date: September 6, 2016

Newspaper: The Dominion Post

Date Application Complete: September 15, 2016

Due Date of Final Action: October 30, 2016

Engineer Assigned: Jonathan Carney

Division of Air Quality
601 57th Street SE
Charleston, WV 25304
Phone (304) 926-0475
Fax (304) 926-0479



west virginia department of environmental protection

Earl Ray Tomblin, Governor
Randy C. Huffman, Cabinet Secretary
www.dep.wv.gov

G70-C GENERAL PERMIT ENGINEERING EVALUATION

PREVENTION AND CONTROL OF AIR POLLUTION IN REGARD TO THE CONSTRUCTION, MODIFICATION, RELOCATION, ADMINISTRATIVE UPDATE AND OPERATION OF NATURAL GAS PRODUCTION FACILITIES LOCATED AT THE WELL SITE

APPLICATION NO.: G70-C**221**

FACILITY ID: 061-**00228**

- ☒ CONSTRUCTION
☐ MODIFICATION
☐ RELOCATION

- ☐ CLASS I ADMINISTRATIVE UPDATE
☐ CLASS II ADMINISTRATIVE UPDATE

Description of Permitting Action: Installation and operation of: seven (7) oil and gas wells, seven (7) gas processing units, a gas and water separator, two (2) natural gas-fired compressor engines, two (2) 400 bbl produced water tanks, one (1) 210 bbl produced water tank and one produced water truck load out.

PROCESS DESCRIPTION

The following process description was taken from Registration Application G70-C221:

Natural gas and produced water will be received from seven wells on this location at approximately 600 psi and pass through Gas Processing Units [Emission Units GPU-1 to GPU-7] to avoid ice and methane hydrate formation during subsequent pressure drops. These materials will then pass through a separator where gas and water are separated. There will be two gas-fired engines [Emission Units CE-1 and CE-2] used to drive compressors which will boost the pressure of the production gas to a pressure suitable for injection into the gathering line owned by others. No dehydration units are proposed for this facility. The compressed gas will be metered and routed to a gathering pipeline owned and operated by others.

The produced water will be accumulated in two 400 bbl tanks and a single 210 bbl tank [Emission Units T01-T03], pending truck loading [Emission Unit TL-1] and transportation to facilities owned and operated by others. Produced water will be re-used at subsequent wells or disposed of at a regional disposal facility. Flash, working, and breathing losses from these tanks have been determined to be nominal, based on measurements at a nearby Northeast Energy Well Pad, and will be allowed to vent to atmosphere. There is no condensate generated at this facility. All natural gas fired equipment (GPUs and the compressor engines) use natural gas produced at the site as fuel.

SITE INSPECTION

Site Inspection Date: October 24, 2016

Site Inspection Conducted By: Kirk Powroznik

Results of Site Inspection: The drilling rig was in place and drilling has commenced for the seven (7) wells to be drilled on the pad site. The closest home was greater than three hundred (300) feet from the site.

Did Applicant meet Siting Requirements? From the results of the site inspection it appears that the applicant has met siting requirements.

If applicable, was siting criteria waiver submitted? N/A

Directions to Facility: On top of a hill off of Route 218 directly across from Jess Tennant Road. According to the inspector, the latitude and longitude listed in the permit application appeared accurate.

Overhead Google Earth Image of Facility:



ESTIMATE OF EMISSIONS BY REVIEWING ENGINEER

The following table indicates which methodology was used in the emissions determination:

Emission Unit ID#	Process Equipment	Calculation Methodology (e.g. ProMax, GlyCalc, mfg. data, AP-42, etc.)
GPU-1	Gas Processing Unit	AP-42
GPU-2	Gas Processing Unit	AP-42
GPU-3	Gas Processing Unit	AP-42
GPU-4	Gas Processing Unit	AP-42
GPU-5	Gas Processing Unit	AP-42
GPU-6	Gas Processing Unit	AP-42
GPU-7	Gas Processing Unit	AP-42
CE-1	CAT 3516 compressor engine	Mfr. Data
CE-2	CAT 3516 compressor engine	Mfr. Data
T01	Produced water tank	GWR
T02	Produced water tank	GWR
T02	Produced water tank	GWR
TL-1	Produced water tank loading	API

The total facility PTE for the facility (including fugitive emissions) is shown in the following table:

Pollutant	Facility Wide PTE (tons/year)
Nitrogen Oxides	16.39
Carbon Monoxide	7.11
Volatile Organic Compounds	7.84
Particulate Matter	1.23
Particulate Matter-10/2.5	1.23
Sulfur Dioxide	0.08
Formaldehyde	1.27
Total HAPs	2.91
Carbon Dioxide Equivalent	20,381

Maximum detailed controlled point source emissions were calculated by the applicant and checked for accuracy by the writer and are summarized in the table on the next page.

APPLICANT:			FACILITY NAME:										G70-C			
Emission Point ID#	NO _x		CO		VOC		SO ₂		PM ₁₀		PM _{2.5}		GHG (CO ₂ e)			
	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy		
GPU-1	0.10	0.438	0.084	0.368	<0.01	0.024	<0.01	<0.01	<0.01	0.033	<0.01	<0.033	121	529		
GPU-2	0.10	0.438	0.084	0.368	<0.01	0.024	<0.01	<0.01	<0.01	0.033	<0.01	<0.033	121	529		
GPU-3	0.10	0.438	0.084	0.368	<0.01	0.024	<0.01	<0.01	<0.01	0.033	<0.01	<0.033	121	529		
GPU-4	0.10	0.438	0.084	0.368	<0.01	0.024	<0.01	<0.01	<0.01	0.033	<0.01	<0.033	121	529		
GPU-5	0.10	0.438	0.084	0.368	<0.01	0.024	<0.01	<0.01	<0.01	0.033	<0.01	<0.033	121	529		
GPU-6	0.10	0.438	0.084	0.368	<0.01	0.024	<0.01	<0.01	<0.01	0.033	<0.01	<0.033	121	529		
GPU-7	0.10	0.438	0.084	0.368	<0.01	0.024	<0.01	<0.01	<0.01	0.033	<0.01	<0.033	121	529		
CE-1	1.52	6.66	0.52	2.27	0.76	3.33	0.01	0.03	0.11	0.50	0.11	0.50	1748	7655		
CE-2	1.52	6.66	0.52	2.27	0.76	3.33	0.01	0.03	0.11	0.50	0.11	0.50	1748	7655		
T01	-	-	-	-	0.091	0.40	-	-	-	-	-	-	122	537.6		
T02	-	-	-	-	0.091	0.40	-	-	-	-	-	-	122	537.6		
T03	-	-	-	-	0.048	0.21	-	-	-	-	-	-	64.5	282.3		
TL-1	-	-	-	-	0.23	0.049	-	-	-	-	-	-	127.85	274.38		
TOTAL	3.74	16.39	1.63	7.12	1.98	7.89	0.02	0.06	0.22	1.23	0.22	1.00	4779.35	20645.88		

APPLICANT:		FACILITY NAME:										G70-C			
Emission Point ID#	Formaldehyde		Benzene		Toluene		Ethylbenzene		Xylenes		Hexane		Total HAPs		
	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	
GPU-1	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	
GPU-2	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	
GPU-3	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	
GPU-4	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	
GPU-5	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	
GPU-6	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	
GPU-7	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	
CE-1	0.14	0.63	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.30	1.33	
CE-2	0.14	0.63	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.30	1.33	
T01	<0.01	<0.01	<0.01	<0.01	<0.01	0.01	<0.01	0.015	<0.01	0.016	0.01	0.05	0.017	0.078	
T02	<0.01	<0.01	<0.01	<0.01	<0.01	0.01	<0.01	0.015	<0.01	0.016	0.01	0.05	0.017	0.078	
T02	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.02	0.01	0.042	
TL-1	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	
TOTAL	0.28	1.26	<0.01	<0.01	<0.01	0.02	<0.01	0.03	<0.01	0.032	0.02	0.12	0.64	2.86	

REGULATORY APPLICABILITY

45CSR2 (Particulate Air Pollution from Combustion of Fuel in Indirect Heat Exchangers)

The purpose of 45CSR2 (Particulate Air Pollution from Combustion of Fuel in Indirect Heat Exchangers) is to establish emission limitations for smoke and particulate matter which are discharged from fuel burning units.

45CSR2 states that any fuel burning unit that has a heat input under ten (10) MMBTU/hr is exempt from Sections 4 (weight emission standard), 5 (control of fugitive particulate matter), 6 (registration), 8 (testing, monitoring, recordkeeping, reporting) and 9 (startups, shutdowns, malfunctions). However, failure to attain acceptable air quality in parts of some urban areas may require the mandatory control of these sources at a later date. If the individual heat input of all of the proposed fuel burning units are below 10 MMBTU/hr, these units are exempt from the aforementioned sections of 45CSR2. However, the registrant would be subject to the opacity requirements in 45CSR2, which is 10% opacity based on a six minute block average. Fuel burning units greater than 10 MMBTU/hr are ineligible for registration under General Permit G70-C

Emission Unit ID#	Emission Unit Description	Maximum Design Heat Input (MDHI) (MMBTU/hr)
GPU-1	Pride of the Hills Gas Processing Unit	1.0
GPU-2	Pride of the Hills Gas Processing Unit	1.0
GPU-3	Pride of the Hills Gas Processing Unit	1.0
GPU-4	Pride of the Hills Gas Processing Unit	1.0
GPU-5	Pride of the Hills Gas Processing Unit	1.0
GPU-6	Pride of the Hills Gas Processing Unit	1.0
GPU-7	Pride of the Hills Gas Processing Unit	1.0

45CSR6 (To Prevent and Control Air Pollution from the Combustion of Refuse)

45CSR6 prohibits open burning, establishes emission limitations for particulate matter, and establishes opacity requirements. Sources subject to 45CSR6 include completion combustion devices, enclosed combustion devices, and flares.

The facility-wide requirements of the general permit include the open burning limitations §§45-6-3.1 and 3.2.

All completion combustion devices, enclosed combustion devices, and flares are subject to the particulate matter weight emission standard set forth in §45-6-4.1; the opacity requirements in §§45-6-4-3 and 4-4; the visible emission standard in §45-6-4.5; the odor standard in §45-6-4.6; and, the testing standard in §§45-6-7.1 and 7.2.

Enclosed combustion control devices and flares that are used to comply with emission standards of NSPS, Subpart OOOO are subject to design, operational, performance, recordkeeping and reporting requirements of the NSPS regulation that meet or exceed the requirements of 45CSR6.

No enclosed combustion control devices or flares are proposed for this facility

45CSR10 (To Prevent and Control Air Pollution from the Emission of Sulfur Oxides)

45CSR10 establishes emission limitations for SO₂ emissions which are discharged from stacks of fuel burning units. A “fuel burning unit” means and includes any furnace, boiler apparatus, device, mechanism, stack or structure used in the process of burning fuel or other combustible material for the primary purpose of producing heat or power by indirect heat transfer. Sources that meet the definition of “Fuel Burning Units” per 45CSR10-2.8 include GPUs, in-line heaters, heater treaters, and glycol dehydration unit reboilers.

Fuel burning units less than 10 MMBtu/hr are exempt. The sulfur dioxide emission standard set forth in 45CSR10 is generally less stringent than the potential emissions from a fuel burning unit for natural gas. The SO₂ emissions from a fuel burning unit will be listed in the G70-C permit registration at the discretion of the permit engineer on a case-by-case basis. Issues such as non-attainment designation, fuel use, and amount of sulfur dioxide emissions will be factors used in this determination. Fuel burning units greater than 10 MMBTU/hr are ineligible for registration under General Permit G70-C

Fuel burning units burning natural gas are exempt from Section 8 (Monitoring, Recording and Reporting) as well as interpretive rule 10A. The G70-C eligibility requirements exclude from eligibility any fuel burning unit that does not use natural gas as the fuel; therefore, there are no permit conditions for 45CSR10.

Emission Unit ID#	Emission Unit Description	Maximum Design Heat Input (MDHI) (MMBTU/hr)
GPU-1	Pride of the Hills Gas Processing Unit	1.0
GPU-2	Pride of the Hills Gas Processing Unit	1.0
GPU-3	Pride of the Hills Gas Processing Unit	1.0
GPU-4	Pride of the Hills Gas Processing Unit	1.0
GPU-5	Pride of the Hills Gas Processing Unit	1.0
GPU-6	Pride of the Hills Gas Processing Unit	1.0
GPU-7	Pride of the Hills Gas Processing Unit	1.0

45CSR13 (Permits for Construction, Modification, Relocation and Operation of Stationary Sources of Air Pollutants, Notification Requirements, Administrative Updates, Temporary Permits, General Permits, and Procedures for Evaluation)

45CSR13 applies to this source due to the fact that the applicant is defined as a “stationary source” under 45CSR13 Section 2.24.b. *Stationary source* means, for the purpose of this rule, any building, structure, facility, installation, or emission unit or combination thereof, excluding any emission unit which meets or falls below the criteria delineated in Table 45-13B which: (a) is subject to any substantive requirement of an emission control rule promulgated by the Secretary; (b) discharges or has the potential to discharge more than six (6) pounds per hour and ten (10) tons per year, or has the potential to discharge more than 144 pounds per calendar day, of any regulated air pollutant; (c) discharges or has the potential to discharge more than two (2) pounds per hour or five (5) tons per year of hazardous air pollutants considered on an aggregated basis; (d) discharges or has the potential to discharge any air pollutant(s) listed in Table 45-13A in the amounts shown in Table 45-13A or greater; or, (e) an owner or operator voluntarily chooses to be subject to a construction or modification permit pursuant to this rule, even though not otherwise required to do so. 45CSR13 has an original effective date of June 1, 1974.

The applicant meets the definition of a stationary source because (check all that apply):

- ☒ Subject to a substantive requirement of an emission control rule promulgated by the Secretary.
- ☒ Discharges or has the potential to discharge more than six (6) pounds per hour and ten (10) tons per year, or has the potential to discharge more than 144 pounds per calendar day, of any regulated air pollutant.
- ☐ Discharges or has the potential to discharge more than two (2) pounds per hour or five (5) tons per year of hazardous air pollutants considered on an aggregated basis.
- ☐ Discharges or has the potential to discharge any air pollutant(s) listed in Table 45-13A in the amounts shown in Table 45-13A or greater.

- ☐ Voluntarily chooses to be subject to a construction or modification permit pursuant to this rule, even though not otherwise required to do so.

General Permit G70-C Registration satisfies the construction, modification, relocation and operating permit requirements of 45CSR13. General Permit G70-C sets forth reasonable conditions that enable eligible registrants to establish enforceable permit limits.

Section 5 of 45CSR13 provides the permit application and reporting requirements for construction of and modifications to stationary sources. No person shall cause, suffer, allow or permit the construction, modification, relocation and operation of any stationary source to be commenced without notifying the Secretary of such intent and obtaining a permit to construct, modify, relocate and operate the stationary source as required in the rule or any other applicable rule promulgated by the Secretary.

If applicable, the applicant meets the following (check all that apply):

- ☐ Relocation
☐ Modification
☐ Class I Administrative Update (45CSR13 Section 4.2.a)
☐ Class II Administrative Update (45CSR13 Section 4.2.b)

45CSR16 (Standards of Performance for New Stationary Sources Pursuant to 40 CFR Part 60)

45CSR16 applies to all registrants that are subject to any of the NSPS requirements described in more detail in the Federal Regulations section. Applicable requirements of NSPS, Subparts IIII, JJJJ and OOOO are included in General Permit G70-C.

The applicant is subject to:

- ☐ 40CFR60 Subpart IIII
☒ 40CFR60 Subpart JJJJ
☒ 40CFR60 Subpart OOOO

45CSR22 (Air Quality Management Fee Program)

45CSR22 is the program to collect fees for certificates to operate and for permits to construct or modify sources of air pollution. 45CSR22 applies to all registrants. The general permit fee of \$500 is defined in 45CSR13. In addition to the application fee, all applicants subject to NSPS requirements or NESHAP requirements shall pay additional fees of \$1,000 and \$2,500, respectively.

Registrants are also required to obtain and have in effect a valid certificate to operate in accordance with 45CSR22 §4.1. The fee group for General Permit G70-C is 9M (all other sources) with an annual operating fee of \$200.

40CFR60 Subpart IIII (Standards of Performance for Stationary Compression Ignition Internal Combustion Engines)

The facility does not contain an affected source (compression ignition engine) and is therefore not subject to this subpart.

40CFR60 Subpart JJJJ (Standards of Performance for Stationary Spark Ignition Internal Combustion Engines)

Subpart JJJJ sets forth nitrogen oxides (NO_x), carbon monoxide (CO), and volatile organic compound (VOC) emission limits, fuel requirements, installation requirements, and monitoring requirements based on the year of installation of the subject internal combustion engine. The provisions for stationary spark ignition (SI) internal combustion engines for owners or operators of this Subpart have been included in General Permit G70-C, Section 13.

Emission Unit ID#	Engine Description (Make, Model)	Engine Size (HP)	Date of Manufacture	Provide Justification how 40CFR60 Subpart JJJJ is met.
CE-1	CAT 3516B	1380	01/2017	<input checked="" type="checkbox"/> Met Emission Standard <input type="checkbox"/> Certified Engine
CE-2	CAT 3516B	1380	01/2017	<input checked="" type="checkbox"/> Met Emission Standard <input type="checkbox"/> Certified Engine

40CFR60, Subpart OOOO (Standards of Performance for Crude Oil and Natural Gas Production, Transmission and Distribution)

EPA published its New Source Performance Standards (NSPS) and air toxics rules for the oil and gas sector on August 16, 2012. EPA published final amendments to the Subpart on September 23, 2013.

40CFR60 Subpart OOOO establishes emission standards and compliance schedules for the control of volatile organic compounds (VOC) and sulfur dioxide (SO₂) emissions from affected facilities that commence construction, modification or reconstruction after August 23, 2011. The affected sources which commence construction, modification or reconstruction after August 23, 2011 are subject to the applicable provisions of this Subpart as described below:

Gas well affected facilities are included in General Permit G70-C in Section 5.0.

Are there any applicable gas well affected facilities? ☒ Yes ☐ No

If Yes, list.

API number(s) for each Gas Well at this facility	Date the Gas Well was drilled or re-fractured
47-061-01733	01/09/2017 Proposed date
47-061-01734	01/17/2017 Proposed date
47-061-01735	01/25/2017 Proposed date
47-061-01753	02/01/2017 Proposed date
47-061-01736	02/09/2017 Proposed date
47-061-01737	02/17/2017 Proposed date
47-061-01739	02/25/2017 Proposed date

Centrifugal compressor affected facilities are included in General Permit G70-C, Section 11.0.

Are there any applicable centrifugal compressor affected facilities not located at the well site?

☐ Yes ☒ No

Each centrifugal compressor affected facility, which is a single centrifugal compressor using wet seals that is located between the wellhead and the point of custody transfer to the natural gas transmission and storage segment. A centrifugal compressor located at a well site, or an adjacent well site and servicing more than one well site, is not an affected facility under this Subpart.

Reciprocating compressor affected facilities are included in General Permit G70-C, Section 12.0.

Are there any applicable reciprocating compressor affected facilities not located at the well site?

☐ Yes ☒ No

Each reciprocating compressor affected facility, which is a single reciprocating compressor located between the wellhead and the point of custody transfer to the natural gas transmission and storage segment. A reciprocating compressor located at a well site, or an adjacent well site and servicing more than one well site, is not an affected facility under this subpart.

Pneumatic controllers affected facilities are included in General Permit G70-C, Section 10.0.

Are there any applicable pneumatic controller affected facilities? ☐ Yes ☒ No

For the natural gas production segment (between the wellhead and the point of custody transfer to the natural gas transmission and storage segment and not including natural gas processing plants), each pneumatic controller affected facility, which is a single continuous bleed natural gas-driven pneumatic controller operating at a natural gas bleed rate greater than 6 scfh.

Requirements for storage vessel affected facilities are included in General Permit G70-C, Section 7.0.

Determination of storage vessel affected facility status is included in Section 6.0 of General Permit G70-C.

Are there any applicable storage vessel affected facilities? ☐ Yes ☒ No

If No, list any emission reduction devices and control efficiencies used to avoid 40CFR60 Subpart OOOO.

The tanks are for produced water only. The emissions from the tanks are expected to be from flashing of volatiles from the water when pressure is reduced. The potential to emit from the tanks is less than 6 tpy.

Each storage vessel affected facility, which is a single storage vessel located in the oil and natural gas production segment, natural gas processing segment or natural gas transmission and storage segment, and has the potential for VOC emissions equal to or greater than 6 tpy as determined according to this section by October 15, 2013 for Group 1 storage vessels and by April 15, 2014, or 30 days after startup (whichever is later) for Group 2 storage vessels. A storage vessel affected facility that subsequently has its potential for VOC emissions decrease to less than 6 tpy shall remain an affected facility under this subpart.

40CFR63 Subpart HH (National Emission Standards for Hazardous Air Pollutants From Oil and Natural Gas Production Facilities)

This Subpart applies to owners and operators of each triethylene glycol (TEG) dehydration unit that are located at oil and natural gas production facilities. Only area source requirements are included in General Permit G70-C, as defined in §63.761.

For area source applicability, the affected source includes each triethylene glycol (TEG) dehydration unit located at a facility that meets the criteria specified in §63.760(a).

Glycol dehydration unit(s) are included in General Permit G70-C, Section 15.0.

Are there any TEG dehydration unit(s) at this facility? ☐ Yes ☒ No

Are the TEG dehydration unit(s) located within an Urbanized Area (UA) or Urban Cluster (UC)?

☐ Yes ☐ No

Are the glycol dehydration unit(s) exempt from 40CFR63 Section 764(d)? ☐ Yes ☐ No

If Yes, answer the following questions:

The actual annual average flowrate of natural gas to the glycol dehydration unit(s) is less than 85 thousand standard cubic meters per day, as determined by the procedures specified in §63.772(b)(1) of this Subpart. ☐ Yes ☐ No

The actual average emissions of benzene from the glycol dehydration unit process vent(s) to the atmosphere are less than 0.90 megagram per year (1 ton per year), as determined by the procedures specified in §63.772(b)(2) of this Subpart. ☐ Yes ☐ No

40CFR63 Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines)

Subpart ZZZZ establishes national emission limitations and operating limitations for hazardous air pollutants (HAP) emitted from stationary reciprocating internal combustion engines (RICE) located at major and area sources of HAP emissions. This Subpart also establishes requirements to demonstrate initial and continuous compliance with the emission limitations and operating limitations. This section reflects EPA's final amendments to 40 CFR part 63, Subpart ZZZZ that were issued on January 15, 2013 and published in the Federal Register on January 30, 2013.

WVDEP DAQ has delegation of the area source air toxics provisions of this Subpart requiring Generally Achievable Control Technology (GACT). The provisions of this Subpart have been included in this general permit under Section 13.0.

Emission Unit ID#	Engine Description (Make, Model)	Engine Size (HP)	Date of Manufacture	New or Existing under 40CFR63 Subpart ZZZZ?	Provide Justification how 40CFR63 Subpart ZZZZ is met.
CE-1	CAT 3516B	1380	01/2017	New	Commenced construction after June 12, 2006. Shall comply with 40 CFR 60 Subpart JJJJ.
CE-2	CAT 3516B	1380	01/2017	New	Commenced construction after June 12, 2006. Shall comply with 40 CFR 60 Subpart JJJJ.

Are there any engines that fall in the window of being new under 40CFR60 Subpart ZZZZ but manufactured before the applicability date in 40CFR60 Subpart JJJJ? ☐ Yes ☒ No

SOURCE AGGREGATION DETERMINATION

"Building, structure, facility, or installation" is defined as all the pollutant emitting activities which belong to the same industrial grouping, are located on one or more contiguous and adjacent properties, and are under the control of the same person.

Are there surrounding wells or compressor stations under "common control" of the applicant?

☐ Yes ☒ No

Are the properties in question located on "contiguous or adjacent" properties?

☐ Yes ☒ No

Are there surrounding facilities that share the same two (2) digit SIC code?

☐ Yes ☒ No

Final Source Aggregation Decision.

☒ Source not aggregated with any other source.

☐ Source aggregated with another source. List Company/Facility Name:

RECOMMENDATION TO DIRECTOR

The information provided in the permit application, including all supplemental information received, indicates the applicant meets all the requirements of applicable regulations and the applicant has shown they meet the eligibility requirements of General Permit G70-C. Therefore, impact on the surrounding area should be minimized and it is recommended that the facility should be granted registration under General Permit G70-C.

Permit Engineer Signature: _____

Name and Title: Jonathan Carney

Date: October 26, 2016